

Pat nt Abstracts of Japan

PUBLICATION NUMBER : 10294010
PUBLICATION DATE : 04-11-98


APPLICATION DATE : 17-04-97
APPLICATION NUMBER : 09100430

APPLICANT : SUMITOMO CHEM CO LTD;

INVENTOR : YASUNORI YUKIO;

INT.CL. : F21V 9/00 G02B 1/10 H01J 11/02

TITLE : FRONT PLATE FOR PLASMA DISPLAY



ABSTRACT : **PROBLEM TO BE SOLVED:** To reduce deformation due to a temperature difference on top and back surfaces of a front plate and prevent visibility of image from being marred by employing a translucent resin plate having average light beam transparency in a specific wavelength is higher than a specific % and curving this translucent resin plate.

SOLUTION: A material of translucent resin plate employed for a front plate 1 includes an acrylic resin, a polycarbonate resin or the like, and the acrylic resin is optimal because of easiness of processing. A translucent resin plate having average light beam transparency in a wavelength of 450 nm to 650 nm more than 50% is employed. A curved shape of the front plate 1 is shaped in a single or plural curves in which a floating quantity at a center part is within 3 mm to 30 mm utilizing flexibility of the translucent resin plate and using a method of forcible bending processing for forcibly curving the plate at room temperature or the like. Further, when an electromagnetic wave or a short infrared ray generated from a plasma display is shielded as an additional function, an electromagnetic shield layer or a short infrared-ray absorption layer is formed.

COPYRIGHT: (C) JPO